

# Declaration of Performance

## HECO-DoP\_ETA\_05/0010\_MMS\_1504\_EN

1. Unique identification code of the product-type:

**HECO MULTI-MONTI MMS**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Identification acc. ETA 05/0010 Annex A2**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**ETA 05/0010 Annex B1**

<b>Generic Type</b>	Concrete screw made of zinc plated steel
<b>Sizes</b>	7,5 mm; 10 mm; 12 mm; 14 mm; 16 mm
<b>Intendend Use</b>	Use in cracked and uncracked concrete C20/25 to C50/60
<b>Option</b>	Option 1 acc. ETAG 001
<b>Loading</b>	static or quasi-static loading
<b>Durability</b>	dry internal conditions

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**HECO-Schrauben GmbH & Co. KG**

**Dr.-Kurt-Steim-Str. 28**

**78713 Schramberg (Germany)**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

-

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 1**



7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

-

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

The **Deutsche Institut für Bautechnik DIBt**,  
 has issued **ETA 05/0010** on the basis of **ETAG 001**.

The **Otto-Graf-Institut Stuttgart, identification code 0672**,  
 has issued a certificate of conformity of the factory production control with the No. **0672-CPR-0083**,  
 based on the third party tasks as set out in Annex V and the definitions in ETA 05/0010.

9. Declared performance  
**acc. ETA 05/0010**

Essential Characteristics	Design Method	Performance	Harmonized Technical Specification
Characteristic resistance for tension	ETAG 001 annex C	ETA-05/0010, annex C1	ETAG 001-01
Characteristic resistance for shear	ETAG 001 annex C	ETA-05/0010, annex C2	
Minimum spacing and minimum edge distance	ETAG 001 annex C	ETA-05/0010, annex B2	
Displacement for serviceability limit state	ETAG 001 annex C	ETA-05/0010, annex C1 & C2	
Characteristic resistance for tension in case of fire	ETAG 001 annex C	ETA-05/0010, annex C3	
Characteristic resistance for shear in case of fire	ETAG 001 annex C	ETA-05/0010, annex C4	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Schramberg, 01.04.2015

p.p. \_\_\_\_\_

Andreas Hettich,  
 Head of PM/Marketing

